



www.raybarmotorcycles.com

TECHNICAL SPECIFICATION

Engine Specification	
Cooling	Air cooled
Number of Cylinders	1
Type (CG or CB)	CG
Balanced or Non Balanced	Balanced
Displacement/Capacity	199.5CC
Max. Power	11.8kw/8000rpm
Max. Torque	15.5N.m/6000rpm
Bore x Stroke	Φ63.5x63
Compression Ratio	9.5:1
Starting	Electric
Top Speed	≥100
Mileage (Litres/100 kms)	2 L/100kms
Carburetor	PZ30
Engine Oil Grade	SF10W-40

Transmission & Chassis	
Clutch	Wet multi plate
Gear box	5 Speed
Front Sprocket	15
Rear Sprocket	42
Chain Size	428HS
Number of Chain links	124

Suspensión	
Front	Telescopic
Rear	Mono Shocker

Brakes	
Front Brake	Disc
Rear Brake	Disc



Wheels & Tyres	
Wheel Size Front	2.15x17
Wheel Size Rear	3.5x17
Tyre Size Front	90/80-17
Tyre Size Rear	4.6-17
Tyre Type (Tubeless or with Tube)	With tube

Electrical/Control System	
Battery	MF-12V?AH
Head Lamp	12V/8w/15w
Head Lamp Type (Normal/LED)	LED
Tail/Stop Lamp	12V/2w
Tail Lamp Type (Normal/LED)	LED
Turn Signal Lamp	12V/0.5W
Turn Signal Lamp Type (Normal/LED)	LED
Ignition System	CDI
Speedometer	Digital

Dimension	
Length (mm)	2005
Width (mm)	770
Height (mm)	1100
Wheelbase (mm)	1370
Ground Clearance (mm)	145
Fuel Tank Capacity (Litres)	15
Kerb Weight (kg)	120
Loadability 1x40 HQ (Packing FOC parts separately)	87

BISON 200



BISON 200



STYLISH HEADLIGHT WITH LED STRIP



POWERFUL 200 CC NEW GENERATION ENGINE



INTEGRATED FRONT LED TURN LIGHTS



REAR LED TURN LIGHTS



DIGITAL SPEEDOMETER



MONO SHOCKER



REAR HUGGER FENDER



EXPOSED CHASSIS



FRONT AND REAR DISC BRAKE



TYRE WITH BETTER GRIP AND BRAKING



NEW LED REAR LIGHT



FRONT OPTICS WITH LED LAMP



BISON



BISON 200