

Raybar (www.raybarmotorcycles.com () /raybarmoto

TECHNICAL SPECIFICATION

Engine	
Cooling	Air Cooled
lo. of Cylinders	1
ype (CG or CB)	CG
Balanced or Non Balanced	Balanced
Displacement/Capacity	250 CC
Max. Power	10.5kw/7500r/min
Max. Torque	16.5N.m/5500r/min
ore x Stroke	65.5x66.2
Compression Ratio	8.8:1
Starting	Electric/ Kick start
op speed	95 kmph
Mileage	2.9 Litres Per 100kms
Carburetor	PZ30

Transmission & Chassis	
Clutch	Wet Multi Plate
Gear box	5 Speed
Front Sprocket	13
Rear Sprocket	42
Chain size	520
Number of Chain links	106

Suspension		
Front	Telescopic	
Rear	Mono Shocker	9.46
	The state of the s	

akes	
ont Brake	Disc
ar Brake	Drum

Wheels & Tyres	
Wheel Size Front	1.85x19
Wheel Size Rear	2.50×17
Tyre Size Front	100/90-19
Tyre Size Rear	4.6-17
Tyre Type	With Tube
	Mr. Park

_			
	Electrical / Control System		PARTY IN
Ī	Battery	MF-12V9AH	
Ī	Head Lamp	12V/14W	
	Head Lamp Type	LED	
	Tail/Stop Lamp	12V/1.4W/0.3W	
8	Tail Lamp Type	LED	A
Ī	Turn Signal Lamp	12V/1.2W	
	Turn Signal Lamp Type	LED	7
	Ignition system	A/C CDI	St. Marie
	Speedometer	Digital	
Sec.			

Dimension		
Length (mm)	2070	
Width (mm)	815	
Height (mm)	1160	
Wheelbase (mm)	1360	
Ground Clearance (mm)	257	
Fuel Tank Capacity (Litres)	10	
Kerb Weight (Kg)	150	

Authorised Dealer:







FOR THE UNSTOPPABLE FUEGO IN YOU

Bring out the unstoppable you. Fuego 250 isn't just some weekend warrior's plaything but a scorching performer. A high power, air-cooled engine delivers maximum speed and advanced traction control lends Fuego 250 an unmatched stability for off road terrain handling. Ignite the unstoppable fuego within!



Stylish Headlight



Day Time Running Lights on Fuel Tank



ylish raphics



ED ndicators



Digital Speedometer



Mono Shocker



Heat Protector for the Rider



Powerful 250 cc Engine



LED Lamp in Headlighta

Special Treads Pattern for Better Grip and Brake



Front Disc Brake





Mobile Charger

